



4333 Electrode, Tig and Mig

1 PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: 4333 Electrode, Tig and Mig
SDS Number: 03
Revision Date: 5/29/2015
Version: 2
Product Use: Welding
Supplier Details: WELD MOLD COMPANY
750 Rickett Road
Brighton, MI 48116

Emergency: 810-229-9521
Contact: Kelley Henrikson
Phone: 810-229-9521
Fax: 810-229-9580
Email: khenrikson@weldmold.com
Web: www.weldmold.com

2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS):

- Health, Skin corrosion/irritation, 1
- Health, Specific target organ toxicity - Single exposure, 3
- Health, Carcinogenicity, 1
- Health, Specific target organ toxicity - Repeated exposure, 2

GHS Label elements, including precautionary statements

GHS Signal Word: **DANGER**

GHS Hazard Pictograms:



GHS Hazard Statements:

- H314 - Causes severe skin burns and eye damage
- H335 - May cause respiratory irritation
- H350 - May cause cancer
- H373 - May cause damage to organs through prolonged or repeated exposure
- CGA-HG11 - SYMPTOMS MAY BE DELAYED.

GHS Precautionary Statements:

- P232 - Protect from moisture.
- P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
- P271 - Use only outdoors or in a well-ventilated area.
- P280 - Wear protective gloves/protective clothing/eye protection/face protection.
- CGA-PG27 - Read and follow the Safety Data Sheet (SOS) before use.

Hazards not otherwise classified (HNOC) or not covered by GHS

Route of Entry: Eyes; Skin; Inhalation
Target Organs: Throat; Nose, Respiratory system
Inhalation: Short term overexposure to welding fumes may result in discomfort such as: dizziness, nausea, or dryness

or irritation of the nose, throat, lungs, and/or eyes.

ACUTE EFFECTS: Irritating to the nose, throat and respiratory tract.

SUBCHRONIC/CHRONIC TOXICITY

CHRONIC: Chronic overexposure to welding fumes can result in: Chronic respiratory problems, iron build-up in the lungs, bone erosion, reduced pulmonary functions and nervous disorders.

Skin Contact: The bright light produced by the arc can burn skin and eyes

Eye Contact: Fumes may be moderately irritating to the eyes

3 COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients:

Cas#	%	Chemical Name
7782-42-5	0-0.2%	Carbon aka Graphite
1344-28-1	0-2%	Aluminum oxide (Al ₂ O ₃)
1633-05-2	0-0.2%	Carbonic acid, strontium salt (1:1)
7789-75-5	0-1%	Calcium fluoride (CaF ₂)
9004-32-4	0-0.5%	Cellulose
1302-78-9	0-0.3%	Bentonite
7440-32-6	0-0.6%	Titanium
7439-96-5	0-0.5%	Manganese compounds and fumes (as Mn)
7440-21-3	0-50%	Silicon
7440-31-5	0-1%	Tin
7723-14-0	0-0.15%	Phosphorus
7440-50-8	77.83-99.9%	Copper
1317-65-3	0-2.2%	Calcium Carbonate (limestone)
15096-52-3	0-14%	Sodium aluminum fluoride (as F)
1344-09-8	0-4%	Silicic acid, sodium salt

EXPOSURE LIMITS

<u>CHEMICAL NAME</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Carbon aka Graphite	15 mg/m ³ TWA	10 mg/m ³
Aluminum Oxide	10 mg/m ³	10 mg/m ³
Strontium Carbonate	NL	NL
Calcium Fluoride	2.5 mg/m ³ As F	2.5 mg/m ³
Cellulose	10 mg/m ³	10 mg/m ³
Bentonite clay	5 mg/m ³ (Dust)	5 mg/m ³
Titanium dioxide	10 mg/m ³ NL = Not Listed	10 mg/m ³
Manganese compounds	5 mg/m ³	1 mg/m ³
Silicon	10 mg/m ³ * = Total dust, <=Respirable fraction	10 mg/m ³ Total Dust
Tin	2 mg/m ³ TWA	2 mg/m ³ TWA
Phosphorus	NL=Not Listed	.02
Copper	1 mg/m ³	1 mg/m ³
Calcium Carbonate (limestone)	15 mg/m ³	2 mg/m ³
Sodium aluminum fluoride	2.5 mg/m ³ as F	2.5 mg/m ³
Silic acid, sodium salt	NL	NL

4 FIRST AID MEASURES

Inhalation: Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention. Non-irritating.

5 FIRE FIGHTING MEASURES

Welding consumables are not flammable, however the welding arc and sparks will ignite other combustible materials. Do not weld in the presence of combustible materials.

6 ACCIDENTAL RELEASE MEASURES

GENERAL PROCEDURES: Prevent waste from contaminating the surrounding environment. Discard any product, residue, disposable container or liner in an environmentally acceptable manner, in full compliance with federal, provincial, and local regulations.

7 HANDLING AND STORAGE

Storage Requirements: Store in a dry area.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Personal Protective Equipment: HMIS PP, D | Face Shield and Eye Protection, Gloves, Apron

PERSONAL PROTECTION

EYES AND FACE: S39 - Wear eye/face protection

RESPIRATORY: Use sufficient ventilation, local exhaust at the arc, or both to keep the fumes and gases below TLV's in the workers breathing zone. In confined spaces use respirable fume respirator or air-supplied respirator.

PROTECTIVE CLOTHING: The intensity of the arc and the sparks emitted from it can cause severe burns. All skin should be covered.

9 PHYSICAL AND CHEMICAL PROPERTIES

Physical State: The welding consumable discussed herein is composed of a wire strip or solid wire rod with or without a flux based core or outer coating.

10 STABILITY AND REACTIVITY

Hazardous Decomposition: The composition and quantity of welding fumes generated are dependent upon several variables including the base material, base material contaminants and/or coatings (paint, galvanized, etc.) welding process utilized. Other factors that will effect the quantity of fumes available for inhalation are the number of welding operators in a designated work area, the quality of ventilation, the position of the operator with respect to the fume plume, as well as the presence of contaminants in the atmosphere from other manufacturing operations. Reasonably expected fume constituents of this product would include: complex oxides of iron, manganese, silicon, chromium, nickel, molybdenum, calcium, magnesium, and titanium.
COMMENTS: No hazard exists until this product is used in welding.

11 TOXICOLOGICAL INFORMATION

REPRODUCTIVE TOXIN: Not known
MUTAGENICITY: Not known

ENVIRONMENTAL DATA: No data available

Dispose of in accordance with federal, state and local regulations.

SPECIAL SHIPPING NOTES: Special shipping considerations for this product are limited to those necessary to prevent damaging the product.

Component (CAS#) [%] - CODES

Aluminum oxide (Al₂O₃) (1344-28-1) [0-2%] MASS, NJHS, OSHAWAC, PA, SARA313, TSCA, TXAIR

Calcium fluoride (CaF₂) (7789-75-5) [0-1%] TSCA

Silicon (7440-21-3) [0-50%] MASS, OSHAWAC, PA, TSCA, TXAIR

Tin (7440-31-5) [0-1%] MASS, OSHAWAC, PA, TSCA, TXAIR

RQ(5000LBS), Copper (7440-50-8) [77.83-99.9%] CERCLA, EPCRAWPC, MASS, NJHS, OSHAWAC, PA, PRIPOL, SARA313, TOXICPOL, TSCA, TXAIR

Calcium Carbonate (limestone) (1317-65-3) [0-2.2%] MASS, OSHAWAC, PA, TSCA, TXAIR

Sodium aluminum flouride (as F) (15096-52-3) [0-14%] TSCA

Silicic acid, sodium salt (1344-09-8) [0-4%] TSCA


Regulatory CODE Descriptions

RQ = Reportable Quantity
MASS = MA Massachusetts Hazardous Substances List
NJHS = NJ Right-to-Know Hazardous Substances
OSHA WAC = OSHA workplace Air Contaminants
PA = PA Right-To-Know List of Hazardous Substances
SARA313 = SARA 313 Title III Toxic Chemicals
TSCA = Toxic Substances Control Act
TXAIR = TX Air Contaminants with Health Effects Screening Level
CERCLA = Superfund clean up substance
EPCRAWPC = EPCRA Water Priority Chemicals
PRIPOL = Clean Water Act Priority Pollutants
TOXICPOL = Clean water Act Toxic Pollutants


NFPA: Health = 2, Fire = 0, Reactivity = 0, Specific Hazard = n/a

HMIS III: Health = 2(Chronic), Fire = 0, Physical Hazard = 0

HMIS PPE: D - Face Shield and Eye Protection, Gloves, Apron



HMIS	
HEALTH	2
FLAMMABILITY	0
PHYSICAL HAZARD	0
PERSONAL PROTECTION	D



REGULATORY INFORMATION:

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

313 REPORTABLE INGREDIENTS: This product contains some or all of the following reportable ingredients; Copper, Chromium, Manganese and Nickel

TSCA STATUS: All components of this product are listed on or exempt from the TSCA inventory.

"WARNING: This product contains the following chemical(s) known to the state of California to cause cancer: Nickel (metallic) CAS# 7440-02-0"