SAFETY DATA SHEET (SDS) SDS #R500

1. IDENTIFICATION

| Product Type: | Carbon steel and low alloy steel electrodes for arc welding |
|-----------------------------------|---|
| Part Numbers: | 64001200, 64001206, 64001212, 64001218, 64001202, 64001208, 64001214,, 64001218, 64001540, 64001542, 64001544, 64001640, 64001641, 64001642, 64001643, 64001644, 64001645, 64001646, 64001647, 64001648 |
| Specifications: | AWS A5.5, A5.18, A5.28 |
| Product Intended/Recommended Use: | Arc welding |
| Manufacturer: | Radnor Products 259 North Radnor-Chester Road Suite 100 Radnor, PA 19087-5283 |
| Emergency Telephone Number: | +1 (866) 734-3438 |

2. HAZARD IDENTIFICATION

Hazard Classification: Not classified as hazardous according to the applicable Globally Harmonized System of Classification and Labelling of Chemicals (GHS) and OSHA Hazard Communication Standard (29 CFR 1910.1200) criteria.

Label Elements:

Hazard Symbol – None Signal Word – None Hazard Statement – Not Applicable Precautionary Statement – Not Applicable

Other Hazards: This product presents no hazards in its intrinsic form. However, several hazards are generated during welding operations that can be harmful.

ELECTRICITY- Electric shock can kill.

HEAT- Molten metal and weld spatter can burn skin and start fires.

RADIATION- Arc rays can injure eyes and burn skin.

FUMES AND GASES - Fumes and gases generated during welding can be dangerous to your health. See Section

11.

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Common Name | Weight % |
|---------------------------------|----------|
| Iron | 70-98 |
| Manganese | 0-4 |
| Silicon | 0-3 |
| Silica | 0-3 |
| Aluminum | 0-5 |
| Aluminum Oxide | 0-1 |
| Chromium | 0-10.0 |
| Nickel | 0-3 |
| Niobium | 0-0.3 |
| Magnesium and compounds | 0-3 |
| Molybdenum | 0-1.2 |
| Titanium | 0-0.5 |
| Titanium Dioxide | 0-10 |
| Vanadium | 0-0.3 |
| Barium Compounds | 0-10 |
| Lithium Compounds (as Li) | 0-9 |
| Iron Oxide | 0-12 |
| Zirconium and Compounds (as Zr) | 0-1 |
| Fluorides | 0-12 |
| Graphite | 0-0.5 |
| Copper | 0-0.8 |

4. FIRST AID MEASURES

Inhalation - If breathing has stopped, immediately seek medical assistance. Begin performing cardio pulmonary resuscitation (CPR) if you are trained to do so. If breathing is difficult, move to area with fresh air and seek medical attention immediately.

Skin contact - For skin burns due to arc radiation flush with cold water. If burn and irritation persists seek medical attention. In case of skin contact with fume or dust, wash affected areas with soap and water. Thoroughly clean shoes and wash clothing. Seek medical attention if irritation develops and persists.

Eye contact - In case of radiation burns due to arc flash move to a dark room and seek medical attention. To remove fume or dust flush with plenty of lukewarm water. Seek medical attention if irritation develops. In case of foreign metallic or slag material lodged in the eye, seek medical attention to remove it. Do not rub or agitate the eyes.

Ingestion – Although unlikely due to product form, immediately seek medical attention if wire pieces or metal powders from inside the wire are ingested. Do not induce vomiting unless directed to do so by medical personnel.

Electric Shock - Disconnect power. Use non-conductive material to pull victim from contact with live wires. If no detectible pulse, seek medical attention immediately and begin cardio pulmonary resuscitation (CPR) if you are trained to do so.

Most Serious Symptoms:

Short Term Exposure – Acute overexposure to welding fumes may result in discomfort such as irritation of the respiratory system, metal fume fever, nausea, and may aggravate pre-existing respiratory conditions.

Long Term Exposure – Chronic overexposure to welding fume may lead to iron deposits in the lungs (siderosis) and reduced pulmonary function. Manganese overexposure can lead to irreversible damage to the central nervous system resulting in impaired speech and movement. Chronic overexposure to nickel fumes and hexavalent chromium can cause cancer. Some of the products contain silica quartz, but not in an inhalable fraction. Silica quartz is a listed carcinogen.

Refer to Section 11 for more information.

5. FIRE FIGHTING MEASURES

General - Products are non-flammable as shipped. Welding arcs and spatter can ignite nearby combustible materials.

Suitable Extinguishing Media- Use methods and materials appropriate for the combustible material.

Specific Hazards Arising from the Chemical - Welding arcs and spatter can ignite nearby combustible materials.

General Firefighting Procedures- Keep people away. Isolate fire and deny entry to the area by any non-essential personnel. Fight fire from protected location or safe distance.

Special Actions for Firefighters- Firefighters should be equipped with self-contained breathing apparatus to protect against potentially toxic and hazardous fumes. Toxic and irritating fumes and gases may be given off during burning or thermal decomposition.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures:

For Non-Emergency Personnel – Isolate the area and keep non-essential people away. Do not touch or walk through spilled material. Allow the molten metallic material to solidify and cool before disposal. If molten metal spills out of the weldment, turn off the power. Contain the flow using sand or submerged arc flux. If airborne dust and or fumes are present, wear appropriate personal protective equipment (PPE) to avoid overexposure.

For Emergency Personnel – Wear appropriate personal protective equipment (PPE), including clothes, gloves and breathing protection. Evacuate non-essential personnel.

Environmental Precautions: Keep material out of waterways and drains.

Methods and Materials for Containment and Cleaning Up: Isolate and clean up spills immediately. Avoid generating dust or airborne particles during clean up. Dispose of solidified mass per Federal, State and Local regulations.

7. HANDLING AND STORAGE

Precautions for Safe Handling: Wear safety glasses and gloves to avoid cuts and abrasion when handling welding consumables and their packaging. Do not eat drink or smoke in areas where these products are being used.

Conditions for Safe Storage, Including Any Incompatibilities: Store in a cool, dry area in the original packaging. Keep products away from heat, flame and moisture.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Appropriate Engineering Controls: Provide adequate ventilation and/or local exhaust at the weld station to keep fumes and gases away from the welder. Train welders and welding operators to keep their head out of the fumes. See ANSI Z49.1 "Safety in Welding, Cutting, and Allied Processes" for recommendations of safe work practices.

Personal Protective Equipment:

Eye/Face Protection – Wear safety glasses or goggles with appropriate side shields. Wear a helmet or face shield with an appropriate filter lens. Use protective screens to shield others in the work area.

Skin/Body Protection – Wear hand, head and body protection including welder's gloves, protective face shield and long sleeved protective clothing.

Respiratory Protection – Use NIOSH approved fume respirator or air supplied respirator when where ventilation is inadequate, welding in confined spaces or where required to by OSHA regulations. Fume sampling per AWS F1.1 *"Method for Sampling Airborne Particulates Generated by Welding and Allied Processes"* may be required. Other appropriate standards that may be considered include, but are not limited to, AWS F1.2 *"Laboratory Method for Measuring Fume Generation Rate and Total Fume Emission of Welding and Allied Processes"* and AWS F3.2 *"Ventilation Guide for Weld Fume"*. For actual weld fume and particulate analysis, refer to the appropriate analytical methods recommended by NIOSH or OSHA, and consult an industrial hygiene professional.

| Common Name CAS Number | | Form | Exposure Limit | Source | |
|------------------------|------------|-----------------------------|-------------------------|---------------------------|--|
| Aluminum Metal | 7429-90-5 | Total Dust | 15 mg/m ³ | USA. OSHA PELs | |
| | | Total Dust | 10 mg/m ³ | USA. California OSHA PELs | |
| | | Respirable | 5 mg/m ³ | USA. OSHA PELs | |
| | | Respirable | 1 mg/m ³ | USA. ACGIH TLVs | |
| Aluminum Oxide | 1344-28-1 | Total Dust | 15 mg/m ³ | USA. OSHA PELs | |
| | | Respirable | 5 mg/m ³ | USA. OSHA PELs | |
| | | Respirable | 1 mg/m ³ | USA. ACGIH TLVs | |
| Barium Compounds | 7440-39-3 | Soluble Compounds | 0.5 mg/m ³ | USA. OSHA PELs | |
| | | Soluble Compounds | 0.5 mg/m ³ | USA. ACGIH TLVs | |
| Calcium Carbonate | 1317-65-3 | Total Dust | 15 mg/m ³ | USA. OSHA PELs | |
| | | Total Dust | 10 mg/m ³ | USA. California OSHA PELs | |
| | | Respirable | 5 mg/m^3 | USA. OSHA PELs | |
| Chromium | 7440-47-3 | Metal | 1 mg/m ³ | USA. OSHA PELs | |
| | | Metal | 0.5 mg/m ³ | USA. ACGIH TLVs | |
| | | Cr II compounds | 0.5 mg/m ³ | USA. OSHA PELs | |
| | | Cr III Compounds, Inorganic | 0.5 mg/m ³ | USA. OSHA PELs | |
| | | Cr III Compounds, Inorganic | 0.5 mg/m ³ | USA. ACGIH TLVs | |
| | 18540-29-9 | Cr VI Compounds | 0.1 mg/m ³ | USA. OSHA PELs Ceiling | |
| | | Cr VI Compounds, Soluble | 0.005 mg/m ³ | USA. OSHA PELs | |

Control Parameters: Exposure Limits - USA

| | | | (as Cr VI) | |
|-----------------------------|-----------|---------------------------------------|-------------------------|------------------------------|
| | | Cr VI Compounds, Soluble | 0.05 mg/m^3 | USA. ACGIH TLVs |
| | | | (as Cr) | |
| | | Cr VI Compounds, Insoluble | 0.005 mg/m ³ | USA. OSHA PELs |
| | | · · · · · · · · · · · · · · · · · · · | (as Cr VI) | |
| | | Cr VI Compounds, Insoluble | 0.01 mg/m^3 | USA. ACGIH TLVs |
| | | | (as Cr) | |
| Cobalt | 7440-48-4 | As Metal, Dust & Fume | 0.1 mg/m ³ | USA. OSHA PELs |
| | | As Metal, Dust & Fume | 0.02 mg/m ³ | USA. California OSHA PELs |
| | | As Metal, Dust & Fume | 0.02 mg/m ³ | USA. ACGIH TLVs |
| Copper | 7440-50-8 | Dust | 1 mg/m ³ | USA. OSHA PELs & ACGIH TLVs |
| | | Fume | 0.1 mg/m^3 | USA. OSHA PELs |
| | | Fume | 0.2 mg/m ³ | USA. ACGIH TLVs |
| Fluorides | 7789-75-5 | As Fluorides | 2.5 mg/m ³ | USA. OSHA PELs & ACGIH TLVs |
| Iron & Iron Oxide | 1309-37-1 | Iron Oxide (As Fume) | 10 mg/m ³ | USA. OSHA PELs |
| | | Iron Oxide (As Fume) | 5 mg/m ³ | USA. California OSHA PELs |
| | | Respirable | 5 mg/m ³ | USA. ACGIH TLVs |
| Graphite | 7782-42-5 | Total Dust | 15 mg/m ³ | USA. OSHA PELs |
| | | Total Dust | 10 mg/m ³ | USA. California OSHA PELs |
| | | Respirable | 5 mg/m ³ | USA. OSHA PELs |
| | | Respirable | 2 mg/m ³ | USA. ACGIH TLVs |
| Magnesite | 546-93-0 | Total Dust | 15 mg/m ³ | USA. OSHA PELs |
| | | Total Dust | 10 mg/m ³ | USA. California OSHA PELs |
| | | Total Dust | 10 mg/m ³ | USA. ACGIH TLVs |
| | | Respirable | 5 mg/m ³ | USA. OSHA PELs |
| | | Respirable | 2 mg/m^3 | USA. ACGIH TLVs |
| Magnesium Oxide | 1309-48-4 | Fume | 15 mg/m ³ | USA. OSHA PELs |
| 3 | | Fume | 10 mg/m ³ | USA. California OSHA PELs |
| | | Fume (Inhalable) | 10 mg/m ³ | USA. ACGIH TLVs |
| Manganese & Mn Compounds | 7439-96-5 | Fume | 5 mg/m ³ | USA. OSHA PELs Ceiling |
| · | | Fume | 0.2 mg/m ³ | USA. California OSHA PELs |
| | | Fume (Respirable) | 0.02 mg/m ³ | USA. ACGIH TLVs |
| | | Fume (Inhalable) | 0.1 mg/m ³ | USA. ACGIH TLVs |
| | | Inorganic | 5 mg/m ³ | USA. OSHA PELs Ceiling |
| | | Inorganic | 0.2 mg/m ³ | USA. California OSHA PELs |
| | | Inorganic (Respirable) | 0.02 mg/m ³ | USA. ACGIH TLVs |
| | | Inorganic (Inhalable) | 0.1 mg/m ³ | USA. ACGIH TLVs |
| Molybdenum | 7439-98-7 | Soluble Compounds | 5 mg/m ³ | USA. OSHA PELs |
| | | Soluble Compounds | 0.5 mg/m ³ | USA. ACGIH TLVs |
| | | (Respirable) | | |
| | | Insoluble compounds | 15 mg/m ³ | USA. OSHA PELs |
| | | (Total Dust) | 3 | |
| | | Insoluble compounds (Total Dust) | 10 mg/m ³ | USA. California OSHA PELs |
| | | Insoluble compounds | 3 mg/m ³ | USA. ACGIH TLVs & California |
| | | (Respirable) | | OSHA PELs |

| | | Insoluble compounds (Inhalable) | 10 mg/m ³ | USA. ACGIH TLVs |
|--------------------|------------|------------------------------------|-------------------------|---|
| Nickel | 7440-02-0 | Metal | 1 mg/m ³ | USA. OSHA PELs |
| | | Metal (Inhalable) | 1.5 mg/m^3 | USA. ACGIH TLVs |
| | | Metal | 0.015 mg/m ³ | USA. NIOSH RELs |
| | | Soluble Compounds | 1 mg/m ³ | USA. OSHA PELs |
| | | Soluble Compounds | 0.1 mg/m^3 | USA. ACGIH TLVs |
| | | (Inorganic) | | |
| | | Insoluble Compounds | 1 mg/m ³ | USA. OSHA PELs |
| | | Insoluble Compounds | 0.2 mg/m^3 | USA. ACGIH TLVs |
| | | (Inorganic) | | |
| Potassium Silicate | 1312-76-1 | Total | 10 mg/m ³ | USA. ACGIH TLVs |
| Sodium Silicate | 1344-09-8 | Total | 10 mg/m ³ | USA. ACGIH TLVs |
| Silicon | 7440-21-3 | Total Dust | 15 mg/m ³ | USA. OSHA PELs |
| | | Total Dust | 10 mg/m ³ | USA. California OSHA PELs |
| | | Respirable | 5 mg/m ³ | USA. OSHA PELs |
| Silica (Quartz) | 14808-60-7 | Respirable | 0.1 mg/m^3 | USA. OSHA PELs |
| | | Respirable | 0.025 mg/m ³ | USA. ACGIH TLVs |
| | | Total Dust | 0.3 mg/m^3 | USA. OSHA PELs |
| Titanium Dioxide | 13463-67-7 | Total Dust | 15 mg/m ³ | USA. OSHA PELs |
| | | Total Dust | 10 mg/m ³ | USA. ACGIH TLVs |
| Tungsten | 7440-33-7 | Insoluble | 5.0 mg/m^3 | USA. ACGIH TLVs |
| | | Insoluble | 10.0 mg/m ³ | USA. ACGIH TLVs Ceiling |
| | | Soluble | 1.0 mg/m ³ | USA. ACGIH TLVs |
| | | Soluble | 3.0 mg/m ³ | USA. ACGIH TLVs Ceiling |
| Vanadium | 7440-62-2 | Oxide Dust | 0.5 mg/m^3 | USA. OSHA PELs Ceiling |
| | | Oxide Dust (Inhalable) | 0.05 mg/m ³ | USA. ACGIH TLVs & California OSHA PELs |
| | | Oxide Fume | 0.1 mg/m ³ | USA. OSHA PELs Ceiling |
| | | Oxide Fume (Inhalable) | 0.05 mg/m ³ | USA. ACGIH TLVs & California OSHA PELs |
| Zirconium & | 7440-67-7 | Metal | 5 mg/m ³ | USA. ACGIH TLVs |
| Zr Compounds | | | | |
| | | Metal | 10 mg/m ³ | USA. ACGIH TLVs Ceiling |
| | | Compound | 5 mg/m ³ | USA. OSHA PELs |
| | | Compound | 5 mg/m ³ | USA. ACGIH TLVs |
| | | Compound | 10 mg/m ³ | USA. ACGIH TLVs Ceiling |

Exposure Limits – Canada

| Common Name | CAS Number | Form | Exposure Limit | Source |
|----------------------|---------------|------------|--|--|
| Calcium Carbonate | 1317-65-3 | Total Dust | 10 mg/m ³ | Canada. Alberta OEL TWA |
| | | Total Dust | 20 mg/m ³ | Canada. British Columbia OEL TWA STEL |
| | | Total Dust | 10 mg/m ³ | Canada. British Columbia OEL TWA |
| | | Respirable | Respirable 3 mg/m ³ Canada. British Col | |

| | | Total Dust | 10 mg/m ³ | Canada. Saskatchewan OEL for 8hr ACL |
|-----------------------------|------------|----------------------------|-------------------------|--|
| | | Total Dust | 20 mg/m ³ | Canada. Saskatchewan OEL for 15min ACL |
| | | Total Dust | 10 mg/m ³ | Canada. Quebec OEL TWA |
| Manganese & Mn Compounds | 7439-96-5 | As Mn | 0.2 mg/m ³ | Canada. Alberta OEL TWA |
| • | | As Mn | 0.2 mg/m ³ | Canada. British Columbia OEL TWA |
| | | As Mn (Inhalable) | 0.1 mg/m ³ | Canada. Manitoba OEL TWA |
| | | As Mn (Respirable) | 0.02 mg/m ³ | Canada. Manitoba OEL TWA |
| | | As Mn | 0.2 mg/m ³ | Canada. New Brunswick OEL TWA |
| | | As Mn | 0.1 mg/m ³ | Canada. Newfoundland & Labrador OEL TWA |
| | | As Mn | 0.1 mg/m ³ | Canada. Nova Scotia OEL TWA |
| | | As Mn | 1 mg/m ³ | Canada. Nunavut OEL TWA |
| | | As Mn | 3 mg/m ³ | Canada. Nunavut OEL STEL |
| | | As Mn | 5 mg/m ³ | Canada. Nunavut OEL Ceiling |
| | | As Mn | 1 mg/m ³ | Canada. Northwest Territories OEL TWA |
| | | As Mn | 3 mg/m^3 | Canada. Northwest Territories OEL STEL |
| | | As Mn | 5 mg/m ³ | Canada. Northwest Territories OEL Ceiling |
| | | As Mn | 0.2 mg/m^3 | Canada. Ontario OEL TWA |
| | | As Mn | 0.2 mg/m^3 | Canada. Prince Edward Island OEL TWA |
| | | As Mn | 0.2 mg/m^3 | Canada. Quebec OEL TWA |
| | | As Mn | 0.2 mg/m ³ | Canada. Saskatchewan OEL TWA |
| | | As Mn | 0.6 mg/m^3 | Canada. Saskatchewan OEL STEL |
| | | As Mn | 5 mg/m ³ | Canada. Yukon OEL Ceiling |
| Silicon | 7440-21-3 | Total Dust | 10 mg/m ³ | Canada. British Columbia OEL TWA |
| | | Total Dust | 3 mg/m ³ | Canada. New Brunswick OEL TWA |
| | | Total Dust | 10 mg/m ³ | Canada. Nunavut OEL TWA |
| | | Total Dust | 10 mg/m^3 | Canada. Northwest Territories OEL TWA |
| | | Total Dust | 10 mg/m ³ | Canada. Ontario OEL TWA |
| | | Total Dust | 10 mg/m ³ | Canada. Quebec OEL TWA |
| | | Total Dust | 10 mg/m ³ | Canada. Saskatchewan OEL TWA |
| | | Total Dust | 20 mg/m ³ | Canada. Saskatchewan OEL STEL |
| | | Total Dust | 10 mg/m ³ | Canada. Yukon OEL TWA |
| | | Total Dust | 20 mg/m ³ | Canada. Yukon OEL STEL |
| Silica (Quartz) | 14808-60-7 | Respirable Fraction | 0.025 mg/m ³ | Canada. Alberta OEL TWA |
| | | Respirable Fraction | 0.025 mg/m ³ | Canada. British Columbia OEL TWA |
| | | Respirable Fraction | 0.025 mg/m ³ | Canada. Manitoba OEL TWA |
| | | Respirable Fraction | 0.1 mg/m ³ | Canada. Ontario OEL TWA |
| | | Respirable Fraction | 0.05 mg/m ³ | Canada. Quebec OEL TWA |
| | | Respirable Fraction | 0.1 mg/m ³ | Canada. Saskatchewan OEL TWA |
| Titanium Dioxide | 13463-67-7 | Total Dust | 10 mg/m ³ | Canada. Alberta OEL TWA |
| | | Dust (Respirable) | 3 mg/m ³ | Canada. British Columbia OEL TWA |

| Total Dust | 10 mg/m ³ | Canada. British Columbia OEL TWA | |
|------------|----------------------|----------------------------------|--|
| Total Dust | 10 mg/m ³ | Canada. Manitoba OEL TWA | |
| Total Dust | 10 mg/m ³ | Canada. Ontario OEL TWA | |
| Total Dust | 10 mg/m ³ | Canada. Quebec OEL TWA | |
| Total Dust | 10 mg/m ³ | Canada. Saskatchewan OEL TWA | |
| Total Dust | 20 mg/m ³ | Canada. Saskatchewan OEL STEL | |

Exposure Limits – Mexico

| Common Name | ommon Name CAS Form | | Exposure Limit | Source |
|--|----------------------------|----------------------------|-----------------------|-----------------|
| Calcium Carbonate | 1317-65-3 | Total Dust | 20 mg/m ³ | Mexico. OEL CTT |
| | | Total Dust | 10 mg/m ³ | Mexico. OEL CPT |
| Manganese & Mn Compounds | 7439-96-5 | As Mn | 0.2 mg/m ³ | Mexico. OEL CPT |
| | | As Mn Fume | 1.0 mg/m ³ | Mexico. OEL CPT |
| | | | 3.0 mg/m ³ | Mexico. OEL CTT |
| Silicon | Silicon 7440-21-3 Total Du | | 10 mg/m ³ | Mexico. OEL CPT |
| | | Total Dust | 20 mg/m ³ | Mexico. OEL CTT |
| Silica | 69012-46-2 | Fume | 10 mg/m ³ | Mexico. OEL CPT |
| | | Fume (Respirable) | 3 mg/m^3 | Mexico. OEL CPT |
| Silica (Quartz) | 14808-60-7 | Respirable Fraction | 0.1 mg/m^3 | Mexico. OEL CPT |
| Titanium Dioxide 13463-67-7 Total Dust | | 20 mg/m ³ | Mexico. OEL CTT | |
| | | Total Dust | 10 mg/m ³ | Mexico. OEL CPT |

9. PHYSICAL AND CHEMICAL PROPERTIES

| Appearance | Solid or tubular wire |
|-------------------------------------|-----------------------------|
| Color: | Various |
| Odor: | None |
| Odor threshold: | Not Applicable |
| pH: | Not Applicable |
| Melting point | >2000F (1100C) |
| Initial Boiling Point & Range: | Data Not Available |
| Flash point | Data Not Available |
| Evaporation rate | Data Not Available |
| Flammability | Data Not Available |
| Upper flammability/explosive limit: | Data Not Available |
| Lower flammability/explosive limit: | Data Not Available |
| Vapor pressure | Not Applicable |
| Vapor density: | Not Applicable |
| Relative density | 0.2-0.3 lbs/in ³ |
| Solubility in water | Data Not Available |
| Solubility (other) | Data Not Available |
| Partition coefficient | Data Not Available |
| Auto-ignition temperature | Data Not Available |
| Decomposition temperature: | Data Not Available |
| Viscosity : | Data Not Available |

10. STABILITY AND REACTIVITY

Reactivity – This product is not reactive under normal conditions as shipped.

Chemical stability – This product is chemically stable under normal conditions as shipped.

Possibility of hazardous reactions – Polymerization reactions will not occur.

Conditions to avoid – Protect product from moisture and contamination.

Incompatible materials – Data not available

Hazardous decomposition products – Welding electrodes and wires emit fumes and gases when used under normal conditions. These fumes and gases produced during welding operations cannot be easily classified, and will differ in quantity and form from those ingredients listed in Section 3 of this SDS. The composition and quantity of these fumes and gases are directly dependent upon the metal being welded, any material coatings (such as primer or galvanizing), the welding process, the welding consumables and the welding procedures. Other conditions which also influence the composition and quantity of the fumes and gases produced include the number of welders in the work area, the volume of the work area, the quality and amount of ventilation or exhaust, and the proximity of the welder's head to the fume plume.

Decomposition products of welding consumables under normal operation include oxides of elements present in the welding consumable and base material. Manganese compounds may be present in the fume from manganese bearing electrodes. Hexavalent chromium may be present in the fume from electrodes containing chromium. Nickel compounds may be present in the fume from nickel bearing electrodes. Fluoride containing consumables may generate gaseous and particulate fluoride. Gases such as carbon monoxide, carbon dioxide, ozone and nitrogen oxides may also be produced in the arc area.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Oral – Unknown health effects, but this exposure is unlikely to occur.

Inhalation – Inhalation of welding fumes may lead to acute and/or chronic health hazards (see table below).

Skin – Arc rays can burn the skin. Weld fume deposited on the skin may cause irritation (see table below).

Eye – Arc rays can injure the eyes. Weld fume contact with the eyes may cause irritation (see table below).

Information on toxicological effects:

The acute and chronic effects of compounds which may be exposed to the welder are listed in the table below. Also listed are the available measured values of toxicity for that substance and whether is it classified as carcinogenic.

| Substance | Short-Term Exposure Effects | Long Term Exposure Effects | Toxicity Measure | Carcinogenicity |
|-------------|--------------------------------|----------------------------------|------------------|------------------|
| Aluminium | May cause eye & respiratory | May cause effects on central | LC50 (Rat, Oral | Not classifiable |
| Oxide | irritation. | nervous system. | Exposure) | |
| | | | >5,000 mg/kg | |
| Barium | May cause irritation to the | May cause baratosis (deposits of | LD50 (Rat, Oral | Not classifiable |
| Compounds | nose, throat, and respiratory | barium in lungs). Baratosis is | Exposure) | |
| | tract. | benign & does not progress to | = 418 mg/kg | |
| | | fibrosis. | | |
| Chromium as | May cause eye, skin & | May cause chronic bronchitis, | LC50 (Rat,14 day | Not classifiable |
| Cr+3 | respiratory irritation. | sinusitus, rhinitus and ashtma. | Oral Exposure) | |
| | | | >5,000 mg/kg | |

| Chromium as | May cause eye, skin & | May cause lung, nasal and sinus | LC50 (Rat ,Oral | IARC-1 |
|-----------------------|--|---|--|---------------------|
| Cr+6 | respiratory irritation. | cancer, ulceration and | Exposure) | NTP-known |
| | | perforation of the nasal septum and skin rash. | = 29 mg/kg | OSHA |
| Cobalt | May cause respiratory | May cause chronic irritation, | LC50 (Rat, 30 min | Not classifiable |
| Compounds | irritation and cardiovascular inflammation. | diminished pulmonary function, asthma and fibrosis. | Inhalation Exposure) = 165mg/m ³ | |
| Substance | Short-Term Exposure Effects | Long Term Exposure Effects | Toxicity Measure | Carcinogenicity |
| Copper Oxide | May cause metal fume fever with upper respiratory irritation, chills, and aching muscles. | Prolonged contact may cause skin sensitization. | LD50 (Rat, Oral Exposure) = 470mg/kg | Not classifiable |
| Fluorides | May cause eye, skin & respiratory irritation. | May cause serious bone erosion and mottling of teeth (fluorosis). | LD50 (Rat, Oral Exposure) = 31 mg/kg | Not classifiable |
| Iron Oxide | May cause respiratory irritation. | May cause siderosis (deposits of iron in lungs). Siderosis is benign and does not progress to fibrosis. | LD50 (Rat, Oral Exposure) > 10,000 mg/kg | Not classifiable |
| Lithium Compounds | May cause eye & skin irritation. | May adversely affect the central nervous system & kidneys, and may be a reproductive toxin. | LC50 (Rat, 4 hour Inhalation Exposure) > 2.17 mg/L | Not classifiable |
| Magnesium Oxide | May cause eye & respiratory irritation. | May cause decreased lung function. | LD50 (Rat, Oral Exposure) = 3870 mg/kg | Not classifiable |
| Manganese Oxide | May cause respiratory irritation, metal fume fever with chills, fever, upset stomach, body ache, vomiting. | May cause brain and central nervous system effects resulting in arm and leg tremors, slurred speech and poor coordination. | LD50 (Rat, 4 hour Inhalation Exposure) = 19 mg mg/kg | Not classifiable |
| Molybdenum | May cause eye & respiratory irritation. | Not found. | Not found | Not classifiable |
| Nickel Oxide | May cause respiratory irritant, inhalation of fumes may cause pneumonitus. | Prolonged exposure may lead to asthma. Nickel refinery workers showed a higher incidence of lung and nasal cancers. | LD50 (Rat, Inhalation Exposure) > 5,000 mg/kg | IARC-1 NTP-known |
| Niobium | May cause respiratory irritation. | Not found. | Not found | Not classifiable |
| Silica | May cause eye & respiratory irritation. | Crystalline silica is a known carcinogen. Overexposure may also result in silicosis. | Not found | IARC-1 NTP-known |
| Titanium Dioxide | May cause respiratory irritation. | May be carcinogenic. | LD50 (Rat, Oral Exposure) > 10 g/kg | IARC-2B |
| Tungsten compounds | May cause respiratory irritation. | Not found. | Not found | Not found |
| Vanadium Oxide | May cause eye, skin & respiratory irritation. | Exposure to high concentrations of fume may lead to chronic nasal hyperplasia. | LD50 (Rat, Oral Eposure) =10 mg/kg | Not classifiable |
| Zirconium Oxide | May cause eye & respiratory irritation. | May cause decreased lung function. | Not found | Not classifiable |
| Carbon Dioxide | At low levels, may cause headache, dizziness, loss of coordination, nausea. At | Long term exposure may affect the body's metabolism. | LC50 (Human, Inhalation Exposure) =100,000 ppm/min | Not classifiable |

| | high levels can cause coma and possibly death. | | | |
|---------------------|---|--|--|------------------|
| Carbon Monoxide | May cause effects on the blood, resulting in carboxyhaemoglobinemia and cardiac disorders. High levels may result in death. | May have effects on the cardiovascular system and central nervous system. May cause toxicity to human reproduction or development. | LC50 (Rat, 4 hour Inhalation Exposure) =1807 ppm | Not classifiable |
| Substance | Short-Term Exposure Effects | Long Term Exposure Effects | Toxicity Measure | Carcinogenicity |
| Ozone | May cause eye and respiratory tract Irritation. Inhalation may cause lung oedema. May cause effects on the central nervous system, resulting in headache and impaired performance. | May cause decreased lung function. | LC50 (Rat, 3 hour Inhalation Exposure) =4.5 mg/m3 | Not classifiable |
| Nitric Oxide | May cause respiratory irritation. Inhalation may cause lung oedema. Exposure far above the OEL may result in death. | May cause decreased lung function. | LC50 (Rat, Inhalation Exposure) =160 mg/m ³ | Not classifiable |
| Nitrogen Dioxide | Corrosive to the skin and respiratory tract. Inhalation may cause lung oedema. Exposure far above the OEL may result in death. | May cause effects on the immune system and lungs, resulting in decrease in resistance to infection. | LC50 (Rat, 4 hour Inhalation Exposure) =88 ppm | Not classifiable |

Other information on toxicological effects:

Germ cell mutagenicity – Not classified Reproductive toxicity – Not classified Specific target organ toxicity (Single exposure) – Not classified Specific target organ toxicity (Repeated exposure) – Not classified Aspiration hazard – Not classified

12. ECOLOGICAL INFORMATION

| Toxicity: | Not classified |
|--------------------------------|--------------------------|
| Persistence and degradability: | No information available |
| Bioaccumulative potential: | No information available |
| Mobility in soil: | No information available |
| Other adverse effects: | Unknown |
| | |

13. DISPOSAL CONSIDERATIONS

Discard any product, residue, waste or packaging in an environmentally acceptable manner in compliance with federal, State, or local laws. Do not dispose of any waste, remaining product or by-product in the sewer.

| 14. TRANSPORT INFORMATION | |
|---------------------------|--|
|---------------------------|--|

| UN Number: | Not regulated |
|--------------------------|---------------|
| UN Proper Shipping Name: | Not regulated |

| Transport Hazard Class: | Not regulated |
|-------------------------|---------------|
| Packing Group: | Not regulated |
| IMDG: | Not regulated |
| ICAO/IATA: | Not regulated |

15. REGULATORY INFORMATION

U.S. Federal Regulations:

Emergency Planning & Community Right-To-Know Act (EPCRA) of 1986

Section 313 Hazardous Chemicals:

Aluminum, Aluminum Oxide, Barium and Barium Compounds, Chromium, Copper, Lithium Carbonate, Manganese, Nickel, Silicon & Silica, Iron & Iron Oxide, Magnesium, Zirconium and Vanadium.

Superfund Amendments and Reauthorization Act of 1986 (SARA):

Hazard categories – Acute (Immediate) and Chronic (Delayed)

Toxic Substances Control Act (TSCA) Inventory: Iron – Listed Silicon – Listed

U.S. State Laws:

California Proposition 65:

Titanium Dioxide - Carcinogenic

Silica (Quartz) - Carcinogenic

Warning: These products contain chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

New Jersey Community Worker and Right-to-Know Act Titanium Dioxide – Listed Manganese – Listed

Massachusetts Right-to-Know Act Substance List Titanium Dioxide – Listed Manganese – Listed Silica (Quartz) – Listed Pennsylvania Right-to-Know Act Hazardous Substances List Titanium Dioxide – Listed Manganese – Listed

Rhode Island Right-to-Know Act Substance List

Manganese – Listed

Minnesota Right-to-Know Act Hazardous Substances List Titanium Dioxide – Listed Manganese – Listed Silica (Quartz) – Listed

Canadian Regulations:

This product is classified according to the requirements of the Canadian Controlled Products Regulations Section 33, and this SDS contains all required information.

16. OTHER INFORMATION

DISCLAIMER: Users should take all standard and reasonable precautions when using this product for its intended use. The manufacturer does not recommend this product for any uses other than that described. The manufacturer makes no claims and provides no warranty for non-standard use.

| NFPA 704: | HEALTH: | 2 | FLAMMABILITY: | 0 | REACTIVITY: | 0 |
|-----------|---------|---|---------------|---|--------------------|---|
| HMIS: | HEALTH: | 2 | FLAMMABILITY: | 0 | PHYSICAL HAZARD: | 0 |

SDS Revisions

| Preparation date: | 5/12/2017 | Revision date: | Revision | |
|-------------------|-----------|----------------|----------|--|
| | | | number: | |

Note: Although the information and recommendations set forth herein (hereinafter "information") are presented in good faith and believed to be correct as of the date hereof, the manufacturer makes no representations as to the completeness or accuracy thereof. Information is supplied upon the condition that persons receiving same will make their own determination as to its suitability for their purposes prior to use. In no event will the manufacturer be responsible for damages of any nature whatsoever resulting from the use of, misuse or reliance upon information. No representations or warranties, either express or implied, or merchantability, fitness for a particular purpose or any other nature are made hereunder with respect to information or the product to which information refers. Regulatory requirements are subject to change and may differ from one location to another. It is the buyer's responsibility to ensure its activities comply with federal, State, Provincial, and local laws and regulations.